





Screenpod Design & Manufacturing reserves the right to make changes to the information and design of the machines on this document without reservation and notification to the users. Information at time of print considered accurate - Screenpod Design & Manufacturing assumes no liability resulting from errors or omissions in this document

www.screenpod.co.uk



S45RT 2000L

Technical Specifications

The Screenpod S45RT 2000L Dust Suppression Cannons are built to last! Equipped with a strong chassis frame, these machines are perfect for demolition, steel and rental industries.

SPECIFICATIONS\$45Fan motor rating7.5kWPump motor rating2.2kW

Water pump >5.5 bar with run dry protection

Filter system 300 micron 1" filter system

Genset 20 kVA, on-board

Oscillating motor rating 0.18kW

Current consumption 23 Amps

Specified voltage 400-480 AC

Frequency 50/60Hz

Power connector size L1-L2-L3-PE / 32A - 5 pin

Control Panel Start/Stop – Tilt up/down – Turn left/right –

Auto turn on/off - Turn area setting

Throw 45-50m
Water flow 20 - 60 LPM
Elevation, Electric 10 / +50°
Automatic turning system Up to 350°

Fuel capacity 70 Litres

Water tank capacity 2000 Litres

Chassis Galvanised road legal with type approval

DIMENSIONS & WEIGHT

 Length
 5522 mm (18ft 1")

 Width
 1825 mm (6ft 0")

 Height
 2423 mm (7ft 11")

 Dry Weight
 1590 kg (3505 lb)

Office: +44 (0) 28 8775 8944

Email: sales@screenpod.co.uk

Screenpod Design & Manufacturing reserves the right to make changes to the information and design of the machines on this document without reservation and notification to the users. Information at time of print considered accurate - Screenpod Design & Manufacturing assumes no liability resulting from errors or omissions in this document

www.screenpod.co.uk