



Screenpod Design & Manufacturing reserves the right to make changes to the information and design of the machines on this document without reservation and notification to the users. Information at time of print considered accurate - Screenpod Design & Manufacturing assumes no liability resulting from errors or omissions in this document

www.screenpod.co.uk



565 Technical Specifications

The Screenpod S65 Dust Suppression Cannons are built to last! Equipped with a strong chassis frame, these machines are perfect for demolition, steel and rental industries.

SPECIFICATIONS S65 STATIC

Fan motor rating 11kW
Pump motor rating 2.2kW
Oscillating motor rating 0.18kW

Current consumption 23 - 28 Amps

Specified voltage 400V Frequency 50Hz

Power connector size 32A - 4 pin

Control Panel Start/Stop, Raise/Lower, Left/Right, Auto

Oscillate, E-Stop, Radio/Local & Fault Lamps.

Radio remote control (Tele Radio) Start/Stop, Raise/Lower, Left/Right,

Auto Oscillate, E-Stop

Mains cable 10m 4 pin extension cable with inverter plug to

rotate phase direction

Throw 65-80m Water flow 20 - 60 LPM

Water connection Thread I" BSP (DN25)

Required in pressure 2 – 10 bar (min flow of 60 LPM)

Active nozzles Switch between 1 & 4 active nozzles

Elevation, Electric 10° / +50°

Automatic turning system 25° to 350° in steps of 25° Filter system 300 micron 1" filter system

Turning area 350°

Droplet size 10 – 50 microns (mean 70 micron)

DIMENSIONS & WEIGHT

 Length
 1538 mm (5ft 1")

 Width
 1133 mm (3ft 9")

 Height
 2296 mm (7ft 8")

 Dry Weight
 452 kg (996 lb)

Office: +44 (0) 28 8775 8944 **Email:** sales@screenpod.co.uk

Screenpod Design & Manufacturing reserves the right to make changes to the information and design of the machines on this document without reservation and notification to the users. Information at time of print considered accurate - Screenpod Design & Manufacturing assumes no liability resulting from errors or omissions in this document

www.screenpod.co.uk